Quote/Order# Company Name: Attention: Email: Phone#: Job Name: PAIR SINGLE * Single Leaf-- Specify Left or Right Hinge

Fill in Opening Size in the Blanks Provided Above

STANDARD SPECIFICATIONS: Door body 16 gauge stainless steel. $9" \times 14"$ clear acrylic safety window set in black rubber molding. Door assembly includes the original "NO SPRING" Easy Swing® hinges and both $1/4" - 20 \times 1"$ thread cutting screws and #14 - 1 - 1/2" sheet metal/wood screws for jamb by others.

INSTALLATION DETAILS: Jambs must be plumb and square. Minimum double 2 x 4 inch wood construction or equivalent. Hollow metal jambs should be reinforced at hinge locations.

SPECIFIC DETAILS FOR DOOR CONSTRUCTION:

SPECIFIC DETAILS FOR DOOR CONSTRUCTION.	
JAMB GUARD:	[]3"X9"
WINDOW:	[] Standard 9" X 14" In Black Rubber Molding, Up 60" to Center of Window from Floor [] Other:
PLATE:	Specify Height: Color/Material: [] Stainless Steel [] Galvanized Steel [] Black ABS [] Other
BUMPER:	[] Aluminum Bumper Strip
OTHER SPECIFICATIONS:	
APP	ROVED BY: DATE:

Eliason Corporation

DOCUMENT NOT CONTROLLED WHEN PRINTED