## SPEC SHEET P-11 PLUS Quote/Order# **Company Name:** Email: Attention: Job Name: \_\_\_\_\_\_ Phone#: PAIR **SINGLE** CROSS SECTION 60" \* Single Leaf-- Specify Left or Right Hinge Fill in Opening Size in the Blanks Provided Above STANDARD SPECIFICATIONS: Door body consists of 1/2" thick (Expanded PVC material) Inner Frame with Honeycomb Core; high impact exterior thermoplastic surface with a textured finish bonded to both sides. Galvanized steel, powder coated black, back channel. 14" x 16" clear acrylic window set in black rubber molding. Door assembly includes the original "NO SPRING" Easy Swing® hinges and both 1/4" - 20 x 1" thread cutting screws and #14 -1-1/2" sheet metal/wood screws for jamb by others. Hollow metal jambs should be reinforced at hinge locations. SPECIFIC DETAILS FOR DOOR CONSTRUCTION:

**INSTALLATION DETAILS**: Jambs must be plumb and square. Minimum double 2 x 4 inch wood construction or equivalent.

APP	ROVED BY:	DATE:
OTHER SPECIF	ICATIONS:	<u>.</u>
BUMPER:	Standard Black Tear Drop Polyethylene Aluminum Bumper Strip: [ ]	Height: [ ] 12
PLATE:	Specify Height: Color/Material: [ ] Black [ ] Same Color As Door [ ] Stainless Steel [ ] Other	
JAMB GUARD:	ARD: []3" X 9" []5" X 18"	
WINDOW:	[ ] Standard 14" X 16" In Black Rubber Molding, Up 60" to Center of Window from Floor [ ] Other:	
DOOR COLOR:	: [ ] Forest Green [ ] Cadet Blue [ ] White [ ] Metallic Gray [ ] Cloud Gray [ ] Antique White [ ] Chocolate Brown [ ] Red [ ] Medium Brown [ ] Royal Blue [ ] Navy [ ] Black [ ] Beige [ ] Off White [ ] Fudge Brown [ ] Gray	

**Eliason Corporation**