Quote/Order#	SPEC SHEET G-TT PLUS Company Name:
Attention:	Email:
Phone#:	Job Name:
11/ ₁₆ "	PAIR SINGLE 11/16" CROSS SECTION * Single Leaf Specify Left or Right Hinge
1 -	
Fill in Opening Size in the Blanks Provided Above	
STANDARD SPECIFICATIONS: Door body consists of 1/2" thick PVC Inner Frame with Honeycomb Core; high impact exterior thermoplastic surface with a textured finish bonded to both sides. Galvanized steel, powder coated black, back channel. Full perimeter gasketing. 14" x 16" clear acrylic window set in black rubber molding. Door assembly includes the original "NO SPRING" Easy Swing® hinges and both 1/4" - 20 x 1" thread cutting screws and #14 -1-1/2" sheet metal/wood screws for jamb by others.	
INSTALLATION DETAILS : Jambs must be plumb and square. Minimum double 2 x 4 inch wood construction or equivalent. Hollow metal jambs should be reinforced at hinge locations.	
	ILS FOR DOOR CONSTRUCTION: [] Forest Green [] Cadet Blue [] White [] Metallic Gray [] Cloud Gray [] Antique White [] Chocolate Brown [] Red [] Medium Brown [] Royal Blue [] Navy [] Black [] Beige [] Off White [] Fudge Brown [] Gray
WINDOW:	[] Standard 14" X 16" In Black Rubber Molding, Up 60" to Center of Window from Floor [] Other:
JAMB GUARD:	[]3" X 9" []5" X 18"
PLATE:	Specify Height: Color/Material: [] Black [] Same Color As Door [] Stainless Steel [] Other
BUMPER:	Standard Black Tear Drop Polyethylene Height: [] 12 [] 18 [] 24 [] 30 [] 36 [] 42 Aluminum Bumper Strip: []
OTHER SPECIFICATIONS:	

DATE:

Fax: 800-828-3577

APPROVED BY:

Phone: 800-828-3655