Quote/Order#	(	Company Name			
Attention	<u>-</u> <u>I</u>	Email			
Phone#	<u>.</u>	Job Name			
Check One Box for Desired Option					
		CLEAR OPENING HEIGHT			
OPTION A OPTION B OPTION C		FINISHED OPENING WIDTH			
(STANDARD NO (CONTOURED (CONTOURE	ED	1	8" to 29.625"	29.6875" to 35.625"	35.6875" to 48
CONTOUR) TOP & BOTTOM) TOP ONLY	,	OPTION B	FOH+6"	FOH+8"	FOH+10"
	T	OPTION C	FOH+3"	FOH+4"	FOH+5"
	EAR		*FC	OH denotes Finished	Opening Heigh
HEIGHT HEI	IGHT	MAX OPENING HEIGHT			
OPENEING OPENING OPENING HEIGHT HEIGHT			FINISHED OPENING WIDTH		
HEIGHT		18	3" to 29.625	29.6875" to 35.625"	35.6875" to 48"
	1   1	OPTION A	49	49	49
	I	OPTION B	43	41	39
		OPTION C	46	45	44
	deb Once	sing Hoight and Ha	ndina belo	W.	
	_	"t include selected	contour)		
(Opening Heig	_	't include selected	_	OR3	/8"
(Opening Heig	ht doesn	't include selected	contour)	OR3	/8"  OPENING HEIGHT
Opening Heig	ht doesn	1/2"	contour)	OR3	OPENING

**STANDARD SPECIFICATIONS**: Door body 3/4" moisture resistant solid wood core with High Pressure Laminate (HPL) finish on both sides and full perimter black drive in T-molding trim. Straight cut (no countours) is standard. Door assembly includes the original Easy Swing® hinges. (FO Height Minimum 24", For Maximum see table.)

SINGLE

**INSTALLATION DETAILS**: Jambs must be plumb and square. Minimum double 2 x 4 inch wood construction or equivalent. Hollow metal jambs should be reinforced at hinge locations. Fasteners for mounting to jamb included.

ROSS SECTION
· · · · · · · · · · · · · · · · · · ·
3/4" —
/

Specify Laminate:	
Additional Specifications:	

PAIR

APPROVED BY: \_\_\_\_\_ DATE: \_\_\_\_\_

**Eliason Corporation - Senneca Holdings**