SPEC SHEET SCP-CAFÉ/GATE WITH POST Quote/Order# **Company Name** Attention **Email** Phone# **Job Name Check One Box for Desired Option CLEAR OPENING HEIGHT** FINISHED OPENING WIDTH 18" to 31.125" 31.1875" to 37.125" 37.1875" to 48" OPTION A OPTION B OPTION C FOH+3" FOH+4" FOH+5" OPTION B (STANDARD NO CONTOUR) (CONTOURED TOP ONLY) (CONTOURED **OPTION C** FOH+3" FOH+4" FOH+5" TOP & BOTTOM) *FOH denotes Finished Opening Height **MAX OPENING HEIGHT** CLEAR CLEAR OPENING OPENING FINISHED OPENING WIDTH HEIGHT HEIGHT OPENING 18" to 31.125" 31.1875" to 37.125" 37.1875" to 48" OPENING OPENING HEIGHT HEIGHT HEIGHT OPTION A 54 54 54 OPTION B 48 46 44 **OPTION C** 51 50 49 Fill in Post Height (Finished Opening Height), Handing and Opening Width Below. (Finished Opening Height doesn't include selected contour) DOOR 3/8" 3/8" WIDTH **POST POST HEIGHT** LH or RH **HEIGHT** (FO HEIGHT) (FO HEIGHT) 6" Opening Width Opening Width **PAIR SINGLE** CROSS SECTION STANDARD SPECIFICATIONS: Door body 3/4" moisture resistant composite wood core with High Pressure Laminate (HPL) finish on both sides and full perimter black drive in Tmolding trim. Straight cut (no countours) is standard. Door assembly includes the original Easy Swing® hinges. (FO Height Minimum 24", For Maximum see table.) INSTALLATION DETAILS: Jambs must be plumb and square. Minimum double 2 x 4 inch wood construction or equivalent. Hollow metal jambs should be reinforced at hinge locations. Fasteners for mounting to jamb included. Specify Laminate:

Eliason Corporation - Senneca Holdings

Additional Specifications:

APPROVED BY:

DOCUMENT NOT CONTROLLED WHEN PRINTED

DATE: