



StyleCraft®

Durable Design. Fast Lead Times.

Sleek and classic with countless high pressure laminate choices to complement your décor.

Single-Acting Flush High Pressure Laminate Door

- ✓ Premium look and feel.
- ✓ Design flexibility - wide range of finishes.
- ✓ Scratch, heat, and stain resistant.
- ✓ 20, 45, 60, and 90-minute fire ratings.
- ✓ Low maintenance, easy to clean surface.

Standard lead times as low as 2 weeks.
Need it faster, check out our Express Program!

Contact Us
customer@senneca.com | eliasoncorp.com



ELIASON®
A SENNECA BRAND

StyleCraft[®] : Single-Acting Flush High Pressure Laminate Door

SPEED AND QUALITY

Proven quality and fast lead times customers trust, backed by precision engineering and premium materials. Designed for demanding environments, it offers exceptional durability and consistent performance—for a door that works harder, lasts longer, and arrives when you need it.

DOOR PANEL

5-ply bonded core with high-pressure decorative laminate is built to last, meeting WDMA Extra Heavy-Duty standards for cycles, hinge loading, and screw holding, and is available with 20, 45, 60, and 90 minute fire ratings bearing the Warnock Hersey Mark.

PREP OPTIONS

Doors are prepped per the provided hardware schedule and templates. Some hardware, including concealed vertical rods, is not available—contact customer service to confirm compatibility with other concealed options.

FRAME OPTIONS

Eliason offers both hollow metal and stainless steel frames that can be butt-mounted or wrapped for most wall conditions. The frames are available with a variety of mounting systems.

LITE KITS

Factory installed when ordered, with ¼” clear polycarbonate or tempered glass, set in a low-profile beveled steel frame with black powder coat finish. Stock sizes: 8” × 32” and 24” × 30”; additional sizes and finishes available upon request.

FINISHED OPENING LIMITS

Larger openings available upon request.

	Width	Height		Width	Height
Minimum:	24”	80”	Maximum:	48”	96”

STANDARD STOCKED LAMINATES: *Actual samples should always be requested if color accuracy is key.*

