

## **SPECIFICATIONS:**

DOORS SHOWN AS FLEXIBLE VINYL TRAFFIC DOORS,
DOUBLE ACTING, SHALL BE MODEL 240 UNIFLEX
DOORS AS MANUFACTURED BY CHASE INDUSTRIES,
INC., CINCINNATI, OHIO, TO FIT DOOR OPENING
WIDE BY \_\_\_\_\_ HIGH.

DOOR SHALL BE CONSTRUCTED OF TWO LAYERS OF .117 TEXTURED PVC (USDA APPROVED) WITH ANTI-ABRASION SURFACE, LAMINATED BACK-TO-BACK. BRACKET POCKET AND TOP WIPER SEAL ARE TWO-PLY VINYL COATED NYLON. ALL PERIMETER EDGES AND EDGES OF THE VISION PANEL ARE HEAT SEALED TOGETHER. (SPECIFY COLOR:) ☐ FOREST GREEN ☐ GRAY ☐ CHOCOLATE ☐ RED ☐ MEDIUM BROWN ☐ NAVY ☐ ROYAL BLUE ☐ BLACK

DOOR TO UTILIZE TOP MOUNTED GRAVITY-OPERATED HINGING SYSTEM, COMPLETE WITH 1/2" THICK ZINC WALL BRACKET WITH BEARINGS AND 5/8" DIAMETER STEEL ROD ARM.

□ OPTIONAL 100CRB HINGE

VISION PANELS TO BE CONSTRUCTED OF .160 CLEAR USDA FLEXIBLE PVC MATERIAL, INSTALLED

IN THE CENTER OF EACH DOOR PANEL.

□ 15"x14" - 50 (STANDARD) AT 60" ON CENTER

□ 22"x22" - 50 (OPTIONAL) AT 64" ON CENTER

## VALANCE OPTION:

WHEN HEIGHT IS LESS THAN 6".

CONSTRUCTED OF 2-PLY VINYL COATED NYLON ATTACHED TO .080 x 1 x 1 KYDEX ANGLE OF COLOR THAT MATCHES DOOR.

WHEN HEIGHT IS MORE THAN 6".

CONSTRUCTED OF 2 LAYERS OF .117 PVC ATTACHED TO 1/8" x 1 x 1 ALUMINUM ANGLE ON BOTH SIDES.



## MODEL # 240 UNIFLEX, AIRGARD BIPARTING FLEXIBLE VINYL IMPACT TRAFFIC DOOR ©COPYRIGHT 2000 CHASE INDUSTRIES, INC. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE. 1 800-543-4455 www.chasedoors.com CUSTOMER INFORMATION: DATE: 8/04/00 CHASE APPROVAL FORM # SD4089 REV. A