

DOUBLE ACTING, SHALL BE MODEL 240 UNIFLEX
DOORS AS MANUFACTURED BY CHASE INDUSTRIES,
INC., CINCINNATI, OHIO, TO FIT DOOR OPENING
WIDE BY _____ HIGH.

DOOR SHALL BE CONSTRUCTED OF TWO LAYERS OF .117 TEXTURED PVC (USDA APPROVED) WITH ANTI-ABRASION SURFACE, LAMINATED BACK-TO-BACK. BRACKET POCKET AND TOP WIPER SEAL ARE TWO-PLY VINYL COATED NYLON. ALL PERIMETER EDGES AND EDGES OF THE VISION PANEL ARE HEAT SEALED TOGETHER. (SPECIFY COLOR:) ☐ FOREST GREEN ☐ GRAY □ NAVY □ ROYAL BLUE □ BLACK

DOOR TO UTILIZE TOP MOUNTED GRAVITY-OPERATED HINGING SYSTEM, COMPLETE WITH 1/2" THICK ZINC WALL BRACKET WITH BEARINGS AND 5/8" DIAMETER STEEL ROD ARM.

☐ OPTIONAL 100CRB HINGE

IN THE CENTER OF EACH DOOR PANEL.

 \square 15"x14" - 50 (STANDARD) AT 60" ON CENTER \square 22"x22" - 50 (OPTIONAL) AT 64" ON CENTER

VALANCE OPTION:

WHEN HEIGHT IS LESS THAN 6". CONSTRUCTED OF 2-PLY VINYL COATED NYLON ATTACHED TO .080 x 1 x 1 KYDEX ANGLE OF COLOR THAT MATCHES DOOR. WHEN HEIGHT IS MORE THAN 6". CONSTRUCTED OF 2 LAYERS OF .117 PVC ATTACHED TO 1/8" x 1 x 1 ALUMINUM ANGLE ON BOTH SIDES.



MODEL # 240 UNIFLEX, AIRGARD BIPARTING w/TRANSOM Chase Doors FLEXIBLE VINYL IMPACT TRAFFIC DOOR @COPYRIGHT 2000 CUSTOMER INFORMATION: CHASE INDUSTRIES, INC. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE. DATE: 8/04/00 | CHASE APPROVAL 1 800-543-4455 REV. FORM # SD4169 www.chasedoors.com