Attention: Fill in Opening Size in the Blanks Provided Above STANDARD SPECIFICATIONS: Door body is made of 2 layers of .120 textured PVC. Window is 15" x 14" clear PVC. Door assembly consists of all panel components being glued together. Gasket on top edge. Hardware is a wall-mounted bracket with stainless steel arm. Panel is through-bolted to arm with 1/4" hardware. INSTALLATION DETAILS: Jambs must be plumb and square. Minimum double 2 x 4 inch wood construction or equivalent. Hollow metal jambs should be reinforced at hinge locations. SPECIFIC DETAILS FOR DOOR CONSTRUCTION: WINDOW:	Quote/Order#	AIRGARD 240 ORDER FROM Company Name:
Fill in Opening Size in the Blanks Provided Above STANDARD SPECIFICATIONS: Door body is made of 2 layers of .120 textured PVC. Window is 15" x 14" clear PVC. Door assembly consists of all panel components being glued together. Gasket on top edge. Hardware is a wall-mounted bracket with stainless steel arm. Panel is through-bolted to arm with 1/4" hardware. INSTALLATION DETAILS: Jambs must be plumb and square. Minimum double 2 x 4 inch wood construction or equivalent. Hollow metal jambs should be reinforced at hinge locations. SPECIFIC DETAILS FOR DOOR CONSTRUCTION: WINDOW: [] Standard 15" x 14" Clear PVC Window, 60" FFL [] 14" x 16" [] 22" x 22" [] 14" x 16" Visigard [] Other:	-	
Fill in Opening Size in the Blanks Provided Above STANDARD SPECIFICATIONS: Door body is made of 2 layers of .120 textured PVC. Window is 15" x 14" clear PVC. Door assembly consists of all panel components being glued together. Gasket on top edge. Hardware is a wall-mounted bracket with stainless steel arm. Panel is through-bolted to arm with 1/4" hardware. INSTALLATION DETAILS: Jambs must be plumb and square. Minimum double 2 x 4 inch wood construction or equivalent. Hollow metal jambs should be reinforced at hinge locations. SPECIFIC DETAILS FOR DOOR CONSTRUCTION: WINDOW: [] Standard 15" x 14" Clear PVC Window, 60" FFL [] 14" x 16" [] 22" x 22" [] 14" x 16" Visigard [] Other: [] 12 [] 18 [] 24 [] 30 [] 36 [] 40 [] 42 [] 48 Color/Material: [] ABS [] Polyolefin [] Texture PVC PLATE COLOR: [] Black [] Colored (List of colors available upon request) SPECIFIC DETAILS FOR DOOR SHIPMENT: [] Door to Be Skidded [] Door to Be Crated OTHER SPECIFICATIONS:	Phone#:	Job Name:
assembly consists of all panel components being glued together. Gasket on top edge. Hardware is a wall-mounted bracket with stainless steel arm. Panel is through-bolted to arm with 1/4" hardware. INSTALLATION DETAILS: Jambs must be plumb and square. Minimum double 2 x 4 inch wood construction or equivalent. Hollow metal jambs should be reinforced at hinge locations. SPECIFIC DETAILS FOR DOOR CONSTRUCTION: WINDOW: [] Standard 15" x 14" Clear PVC Window, 60" FFL [] 14" x 16" [] 22" x 22" [] 14" x 16" [] 22" x 22" [] 14" x 16" [] 12" x 22" [] 18 [] 24 [] 30 [] 36 [] 40 [] 42 [] 48 Color/Material: [] ABS [] Polyolefin [] Texture PVC PLATE COLOR: [] Black [] Colored (List of colors available upon request) SPECIFIC DETAILS FOR DOOR SHIPMENT: [] Door to Be Skidded [] Door to Be Crated OTHER SPECIFICATIONS:	STANDARD SPEC	Fill in Opening Size in the Blanks Provided Above
SPECIFIC DETAILS FOR DOOR CONSTRUCTION: WINDOW: [] Standard 15" x 14" Clear PVC Window, 60" FFL [] 14" x 16" [] 22" x 22" [] 14" x 16" Visigard [] Other:	assembly consists with stainless stee	of all panel components being glued together. Gasket on top edge. Hardware is a wall-mounted bracket el arm. Panel is through-bolted to arm with 1/4" hardware. DETAILS: Jambs must be plumb and square. Minimum double 2 x 4 inch wood construction or equivalent.
PLATE: Height: [] 12 [] 18 [] 24 [] 30 [] 36 [] 40 [] 42 [] 48 Color/Material: [] ABS [] Polyolefin [] Texture PVC PLATE COLOR: [] Black [] Colored (List of colors available upon request) SPECIFIC DETAILS FOR DOOR SHIPMENT: [] Door to Be Skidded [] Door to Be Crated OTHER SPECIFICATIONS:		
Color/Material: [] ABS [] Polyolefin [] Texture PVC PLATE COLOR: [] Black [] Colored (List of colors available upon request) SPECIFIC DETAILS FOR DOOR SHIPMENT: [] Door to Be Skidded [] Door to Be Crated OTHER SPECIFICATIONS:		
[] Door to Be Skidded [] Door to Be Crated OTHER SPECIFICATIONS:	Colo	or/Material: [] ABS
OTHER SPECIFICATIONS:	SPECIFIC DETAIL	LS FOR DOOR SHIPMENT:
		[] Door to Be Skidded [] Door to Be Crated
	OTHER SPECIFICAT	TIONS:
APPROVED BY: DATE:		ROVED BY: DATE:
Chase Corporation DOCUMENT NOT CONTROLLED WHEN PRINTED		Chase Corporation