AIRGARD 100 ORDER FROM			
Quote/Order#	Company Name:		
Attention:	Email:		
Phone#:	Job Name:		
	FLUSH 60"		
3" DOOR OVERLAP TO SEAL Fill in Opening Size in the Blanks Provided Above			
STANDARD SPECIFICATIONS: Door body is made of 1 layer of 40 Oz Vinyl . Window is 22" x 22" clear polycarbonate. Door assembly consists of all panel components being glued together. Full perimeter panel seal. Hardware is a wall-mounted bracket with stainless steel arm. Panel is through-bolted to arm with 1/4" hardware.			
INSTALLATION DETAILS: Jambs must be plumb and square. Minimum double 2 x 4 inch wood construction or equivalent. Hollow metal jambs should be reinforced at hinge locations. SPECIFIC DETAILS FOR DOOR CONSTRUCTION: HANDING: [] RIGHT [] PAIR			
	[] Standard 22" x 22" Clear PVC Window, 60" FFL		
PLATE: Height: [] 12			
PLATE COLOR: [] Black [] Colored (List of colors available upon request)			
SPECIFIC DETAIL	LS FOR DOOR SHIPMENT: [] Door to Be Skidded [] Door to Be Crated		
OTHER SPECIFICATIONS:			
APPR	ROVED BY: DATE: Chase Corporation		