PROLINE 300I ORDER FORM Company Name: Quote/Order# Email: Attention: Phone#: Job Name: **SINGLE** PAIR 1 3/8" **CROSS SECTION** 60" 1 1/2" Fill in Opening Size in the Blanks Provided Above STANDARD SPECIFICATIONS: Door body is 1-1/2" thick with high impact, thermoplastic material surface, bonded to a high strength PVC frame with a foam core. Provided with full perimeter seal. Variety of window frame sizes available. Door assembly includes the Retailer V-Cam Hardware. INSTALLATION DETAILS: Jambs must be plumb and square. Minimum double 2 x 4 inch wood construction or equivalent. Hollow metal jambs should be reinforced at hinge locations. **SPECIFIC DETAILS FOR DOOR CONSTRUCTION:** HANDING: [] Left [] Right [] Pair DOOR COLOR: [] Forest Green [] Cadet Blue [] White [] Metallic Gray [] Cloud Gray $[\] \ Chocolate \ Brown \ [\] \ Red \ [\] \ Medium \ Brown \ [\] \ Royal \ Blue \ [\] \ Navy \ [\] \ Black \ [\] \ Beige$ [] Off White [] Fudge Brown [] Gray FRAMED WINDOW: [] 10 X 16 [] 10 X 30 [] 12 X 18 [] 16 X 16 [] 17 X 23 [] Other: _____ PLATE: Specify Height: _ Color/Material: [] ABS - Black [] ABS - Same As Door [] Stainless Steel [] Other ______. Standard Black Spring, Height: [] 12 [] 18 [] 24 [] 30 [] 36 [] 42 **BUMPER:** Aluminum Bumper Strip: [] OTHER SPECIFICATIONS:_____ DATE: ____

Chase Doors

800.543.4455

customerservice@senneca.com