

Slide Shut, Bug Out!



**With the economical slide FlexScreen from FlexBarrier —
birds, flies, moths, mosquitoes, gnats, wasps and
other insects are out!**

Fresh air ventilation, sunlight, improved visibility and increased security are in!
And so is employee comfort and improved productivity.

Use the slide FlexScreen at Loading Docks, Garages, Waste Areas and Food Processing Facilities — anywhere you want an economical way to keep bugs and other pests out, but let in sunlight and fresh air!




The easy to install FlexScreen slider can be attached under the header, or mounted to the inside wall with a bracket to allow the screen to be opened beyond the door frame and completely out of the doorway.

Both models feature a simple to use manual roller & track system that allows the FlexScreen to slide smoothly from side to side. Hook and loop fasteners and side seams reinforced with a steel bar completely seal the sides of the FlexScreen and also provide for easy opening and closing.

FlexScreen is made from durable, all-weather vinyl coated polyester which is fire retardant as well as mildew and UV resistant.

The inside wall mount model also incorporates a brush to seal the top against insects.







Quality

- Safety strips sewn into curtain for screen visibility
- Brush made from durable nylon fibers; brush hardware is extruded aluminum
- Nylon rollers; galvanized track; coated steel wall brackets.
- Oversized hook and loop fasteners seal sides tightly and allow for easy opening & closing

Practicality

- Keeps out insects & birds, reduces dust & wind, improves sanitation
- Lets in fresh air and light
- Improves employee comfort and productivity
- Economical to buy and maintain
- Easy to install
- Increases security — a visual and physical barrier to reduce theft & pilferage
- Can be custom ordered to fit almost any opening

Slide FlexScreen Installation & Accessory Hardware

 <p>Hook Rollers are hooks mounted on an axle with two nylon wheels. This provides for easy opening and closing of the FlexScreen.</p>	 <p>Standard Track is straight roller track formed from 16 gauge hot dipped galvanized steel for durability and long life. Attaches quickly and easily to lintel of door opening or wall mount.</p>
 <p>Side Wall Brackets are coated steel angle for years of trouble-free service and are used to attach inside wall mounting.</p>	 <p>Wall Mount Brush is made from nylon fibers. It's used with inside wall mount to seal the top of the FlexScreen — keeping out insects, dust and other contaminants. Extends from top of track over to wall.</p>

FlexBarrier has an extensive line of innovative barrier products to control temperature, dust, humidity, insects, fumes and noise.



P.O. Box 2612
Norcross, GA 30091
FAX 888-884-9667

1-800-277-3539

Visit us on the WEB: www.flexbarrier.com