



Flush Stucco Model 5210 (2" thick R-17.66) Model 5710 (13" thick R-16.18) Decorative Windows p28 Carriage Windows p29 Ranch Windows p30 TL Windows p30 Standard Windows p31



V-Groove Stucco Model 5212 (2" thick R-17.66) Model 5712 (1¾" thick R-16.18) TL Windows p30



Raised Ranch Stucco Panel Model 5270 (2" thick R-17.66) Model 5770 (1¾" thick R-16.18) Decorative Windows p28 Ranch Windows p30



Raised Standard Stucco Panel Model 5280 (2" thick R-17.66) Model 5780 (1¾" thick R-16.18) Decorative Windows p28 Standard Windows p31





A Full Thermal Break is used in the tongue-and-groove construction of all 5000 series doors. This rigid vinyl extrusion seals the joints and eliminates metal-to-metal contact, which limits the transfer of temperature.



5200 series doors include **Air Infiltration Seals**, which exceed the ASHRAE 90.1 Standard when installed with standard bottom seal and commonly available rigid/flexible vinyl door stop.



A Superior Alternative

Mother Nature throws some pretty nasty weather at your home. That's why Haas Door created the 5000 Series: the strength of an insulated garage door combined with long-lasting and corrosion-resistant aluminum. Filled with dense CFC/HCFC- free polyurethane foam insulation, 5200 models are 2 inches thick with a calculated R-value of 17.66, while 5700 models are 1¾ inches thick and have a calculated R-value of 16.18.

5000 Series doors feature a tough, durable and weather-resistant Trinar® paint finish, that carries a 35 year finish warranty. Exposed for decades at weathering facilities in South Florida and other locations around the world, testing has proven Trinar® paints are more than capable of withstanding the degrading effects of weather extremes from the equator to the arctic. Backed by a limited lifetime warranty, the 5000 series is built to last while providing distinction and style.



